

KEY FEATURES

220 Channels for Multi-Constellation GNSS Support

Flexible RS232, USB, Ethernet or CAN Interfacing

Centimeter level position accuracy

Proven Trimble Maxwell 6 technology

Compact Form Factor

COMPACT, LOW-POWER GNSS RECEIVER SPEEDS DEVELOPMENT OF ADVANCED POSITIONING APPLICATIONS.

THE LATEST IN GNSS TECHNOLOGY FROM TRIMBLE IS NOW AVAILABLE TO ORIGINAL EQUIPMENT MANUFACTURERS (OEM) AND SYSTEM INTEGRATORS.

COMPACT FULL METAL JACKET DESIGN

The Trimble® BD970 GNSS system is a compact multi-constellation receiver designed to deliver centimeter accuracy to a variety of applications. With the Trimble BD970, OEM's and integrators can be assured their investment is sound today and into the future. The Trimble BD970 GNSS supports a wide range of satellite signals, including GPS L2C and L5, GLONASS L1/L2 and BeiDou, B1 and B2 signals. In addition, Trimble is committed to the next generation of modernized GNSS configurations by providing Galileo-compatible products available for customers well in advance of Galileo system availability. In support of this plan, the Trimble BD970 is capable of tracking both Galileo signals for evaluation and test purposes.¹

DEMONSTRATED PERFORMANCE

Industry professionals trust Trimble embedded positioning technologies as the core of their precision applications. With the latest Trimble-precise Maxwell™ 6 technology, the BD970 provides assurance of long-term future-proofing and trouble-free operation. Moving the industry forward, the Trimble BD970 redefines high-performance positioning:

- On-board multipath mitigation
- Proven low-elevation tracking technology
- Dramatically improved RTK initialization

FLEXIBLE INTERFACING

The Trimble BD970 was designed for easy integration and rugged dependability. Customers benefit from the Ethernet connectivity available on the board, allowing high speed data transfer and configuration via standard web browsers. USB, RS232 and CAN are also supported. Just like other Trimble embedded technologies, easy to use software commands simplify integration and reduce development times. All software features are password-upgradeable, allowing functionality to be upgraded as your requirements change.

COMPACT DESIGN

The compact form factor is suitable for applications where lightweight is a necessity. The BD970 is rigorously tested to perform in the harsh environments your products are built for, with the reliability you expect from Trimble.



BD970 GNSS RECEIVER

TRIMBLE BD970 GNSS RECEIVER MODULE

TECHNICAL SPECIFICATIONS

- 220 Channels:
 - GPS: Simultaneous L1 C/A, L2E, L2C, L5
 - GLONASS: Simultaneous L1 C/A, L1 P, L2 C/A (GLONASS M Only), L2 P
 - SBAS: Simultaneous L1 C/A, L5
 - Galileo: Simultaneous L1 BOC, E5A, E5B, E5AltBOC¹
 - BeiDou: B1, B2
 - QZSS: L1 C/A, L1 SAI, L2C, L5
- Advanced Trimble Maxwell 6 Custom Survey GNSS Technology
- High precision multiple correlator for GNSS pseudorange measurements
- Unfiltered, unsmoothed pseudorange measurements data for low noise, low multipath error, low time domain correlation and high dynamic response
- Very low noise GNSS carrier phase measurements with <1 mm precision in a 1 Hz bandwidth
- Proven Trimble low elevation tracking technology
- Initialization time² typically <10 seconds
- Initialization reliability² >99.9%
- 1 USB port
- 1 CAN port
- 1 LAN Ethernet port:
 - Supports links to 10BaseT/100BaseT auto-negotiate networks
 - All functions are performed through a single IP address simultaneously—including web GUI access and raw data streaming
 - Network Protocols supported
 - ▶ HTTP (web GUI)
 - ▶ NTP Server
 - ▶ NMEA, GSO, CMR over TCP/IP or UDP
 - ▶ NtripCaster, NtripServer, NtripClient
 - ▶ mDNS/uPnP Service discovery
 - ▶ Dynamic DNS
 - ▶ eMail alerts
 - ▶ Network link to Google Earth
 - ▶ Support for external modems via PPP
- 3 x RS232 ports
 - Baud rates up to 115,200
- 1 Hz, 2 Hz, 5 Hz, 10 Hz, 20 & 50 Hz positioning outputs (depends on installed option)
- Up to 50 Hz raw measurement & position outputs
- Reference outputs/inputs CMR, CMR+, SCMRX, RTCM 2.1, 2.2, 2.3, 3.0, 3.1⁸
- Navigation outputs ASCII: NMEA-0183 GSV, AVR, RMC, HDT, VDG, VHD, ROT, GKG, GGA, GSA, ZDA, VTG, GST, PJT, PJK, BPQ, GLL, GRS, GBS and Binary: Trimble GSO
- Control Software: HTML web browser. Internet Explorer, Firefox, Safari, Opera, Google Chrome
- 1 Pulse Per Second Output
- Event Marker Input Support
- LED drive support 3 (indicating Power, Satellite Tracking, and Differential Data)

POSITIONING SPECIFICATIONS

Mode	Accuracy ⁴	Latency ⁵	Maximum Rate
Single Baseline RTK (<30 km)	0.008 m + 1 ppm Horizontal	<20 ms	50 Hz
	0.015 m + 1 ppm Vertical		
DGPS	0.25 m + 1 ppm Horizontal	<20 ms	50 Hz
	0.50 m + 1 ppm Vertical		
SBAS ⁵	0.5 m Horizontal	<20 ms	50 Hz
	0.85 m Vertical		

PERFORMANCE SPECIFICATIONS

Time to First Fix (TTFF) ⁸	
Cold Start ⁹	<45 seconds
Warm Start ¹⁰	<30 seconds
Signal Re-acquisition	<2 seconds
Velocity Accuracy ^{3,4}	
Horizontal	0.007 m/sec
Vertical	0.020 m/sec
Acceleration	11 g
Maximum Operating Limits ¹¹	
Velocity	515 m/sec
Altitude	18,000 m

PHYSICAL AND ELECTRICAL CHARACTERISTICS

Size	100 mm x 60 mm x 11.6 mm
Power	3.3 V DC +5%/-3%
	Typical 1.4 W (L1/L2 GPS)
	Typical 1.5 W (L1/L2 GPS and G1/G2 GLONASS)
Weight	62 grams
Connectors	
I/O	24-pin header + 6-pin header
Antenna	MMCX receptacle

ENVIRONMENTAL CHARACTERISTICS⁶

Temperature	
Operating	-40 °C to +75 °C
Storage	-55 °C to +85 °C
Vibration	MIL810 F, tailored
	Random 6.2 gRMS operating
	Random 8 gRMS survival
Mechanical shock	MIL810D
	±40 g operating
	±75 g survival

ORDERING INFORMATION

Module	Trimble BD970 GNSS available in a variety of configurations from L1 DGPS upwards
Evaluation Kit	Includes interface board and power supply

- 1 Developed under a License of the European Union and the European Space Agency.
- 2 May be affected by atmospheric conditions, signal multipath, and satellite geometry. Initialization reliability is continuously monitored to ensure highest quality.
- 3 1 sigma level, when using Trimble Zephyr 2 antennas.
- 4 At maximum output rate.
- 5 GPS only and depends on SBAS System performance. FAA WAAS accuracy specifications are <5 m 3DRMS.
- 6 Dependent on appropriate mounting/enclosure design.
- 7 Input only network correction.
- 8 Typical observed values
- 9 No previous satellite (ephemerides / almanac) or position (approximate position or time) information.
- 10 Ephemerides and last used position known
- 11 As required by the U.S. Department of Commerce to comply with export licensing restrictions.

Specifications subject to change without notice.

© 2014, Trimble Navigation Limited. All rights reserved. Trimble and the Globe & Triangle logo are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. Maxwell is a trademark of Trimble Navigation Limited. All other trademarks are the property of their respective owners. 11/2014

AMERICAS
TRIMBLE NAVIGATION LIMITED
Integrated Technologies
510 DeGuigne Drive
Sunnyvale, CA 94085 USA
+1-408-481-8000 Phone
Email: americasales-intech@trimble.com

EUROPE & MIDDLE EAST
TRIMBLE NAVIGATION LIMITED
Integrated Technologies
Germany
+49 (6142) 2100-348 Phone
France
+33 2 28 09 3800 Phone
Email: emeasales-intech@trimble.com

CHINA
TRIMBLE NAVIGATION LIMITED
Integrated Technologies
Email: chinasales-intech@trimble.com

ASIA - PACIFIC
TRIMBLE NAVIGATION LIMITED
Integrated Technologies
Email: asiasales-intech@trimble.com

RUSSIA
TRIMBLE NAVIGATION LIMITED
Integrated Technologies
+49 (6142) 2100-348 Phone
Email: rusasales-intech@trimble.com