

KEY FEATURES

120 Channels

Multi-constellation

Multi-frequencies

RTK, Advanced RTK, Dual RTK

Ashtech Z-Blade Technology

- GNSS-centric engine
- GLONASS-only capable



MB800 GNSS RECEIVER

MULTI-CONSTELLATION, MULTI-FREQUENCIES GNSS CENTRIC RECEIVER MODULE

With the MB800, a multi-constellation, multi-frequencies module, Ashtech brings to the OEM market a unique blend of technologies which increases RTK availability and data integrity. Embedded Z-Blade technology ensures powerful performance and a patented way to use multiple GNSS constellations for high-accuracy positioning and surveying solutions. When dependable performances such as raw data quality or real-time positioning are critical, the Ashtech MB800 GNSS module simply delivers!

ASHTECH HIGH-END PERFORMANCE

Embedded Z-Blade GNSS centric technology uses all available GNSS signals equally, without any constellation preference, to deliver fast and stable solutions. This leads to incredibly robust and dependable measurement processing, resulting in optimized field productivity:

- Advanced multi-path mitigation and signal tracking for maximum data reliability
- Fast initialization and centimeter accuracy at long-range
- Full benefit of any available GLONASS satellites to strengthen the GPS solution
- The most compact differential/raw data protocol: Ashtech Optimized Messaging (ATOM)

SEAMLESS INTEGRATION AND FLEXIBILITY

Designed as a drop-in replacement of the MB500 to support existing OEM customers, the MB800 features a variety of output messages, data formats and advanced features for extensive OEM solution interoperability. The MB800 works as a base and as a rover and is available in various GNSS modes to adapt customer needs. All these GNSS modes are available in the same hardware and are simply activated by firmware option activation.

MB800 supports standard and advanced RTK operations such as:

- RTK against a static base, with or without SBAS and GLONASS satellites
- Advanced RTK against an external moving base for relative positioning
- Network RTK using third-party network corrections: VRS, FKP, MAC
- Heading and pitch/roll determination with baseline length auto-calibration against another receiver
- Dual RTK engine which automatically selects the best position available (Hot Standby RTK) or for RTK + Heading or Relative Positioning against another receiver
- Up to 20 Hz fast RTK and raw data output



MB800 GNSS RECEIVER MODULE*

GNSS CHARACTERISTICS

- 120 channels:
 - GPS L1 C/A L1/L2 P-code, L2C, L5
 - GLONASS L1 C/A, L2 C/A code
 - GALILEO E1 and E5 (including GIOVE-A and GIOVE-B test satellites)
 - SBAS L1 code and carrier (WAAS/EGNOS/MSAS)
 - Fully independent code and phase measurement
- Z-Blade technology for optimal GNSS performance:
 - Ashtech GNSS centric algorithm
 - Quick signal detection engine for fast acquisition and re-acquisition of GNSS signals
 - Fast and stable RTK solution
 - Up to 20 Hz real-time raw data, position and heading (against another receiver) output
 - Advanced multi-path mitigation technique
 - RTK base and rovers modes, post-processing

FEATURES

- Up to 20 Hz Real-time GNSS raw data (code and carrier) and position output
- Real-time GNSS sub-frames output
- Ephemeris and almanac for GNSS
- Ionosphere data output
- NMEA0183 messages output
- RTK base and rover modes
- Easy-to-use trouble ticket (ATL)

RTK BASE

- RTCM-2.3 & RTCM-3.1
- CMR & CMR+
- DBEN & ATOM (Ashtech format)
- Moving base operation
- Automatic Base Station Position Averaging

RTK ROVER

- Up to 20 Hz Fast RTK
- RTCM-2.3 & RTCM-3.1
- CMR & CMR+
- DBEN, LRK & ATOM (Ashtech formats)
- Networks: VRS, FKP, MAC
- NMEA0183 messages output
- RTK with moving base operation
- Heading and pitch or roll determination with auto-calibration (against another receiver)

ACCURACY SPECIFICATIONS (RMS)¹

SBAS

- < 50 cm typical Horizontal

DGPS

- < 30 cm + 1 ppm typical Horizontal^{2,3}

FLYING RTK

- 5cm + 1 ppm horizontal (steady state) for baselines up to 1000 km

RTK

- Horizontal: 1 cm + 1 ppm^{2,3}
- Vertical: 2 cm + 1 ppm^{2,3}

HEADING, PITCH/ROLL

- Heading: 0.2 deg/baseline (m)^{2,4}
- Pitch/roll: 0.4 deg/baseline (m)^{2,4}

RTK INITIALIZATION

- Instant-RTK Initialization
 - Typically 2-second initialization for baselines < 20 km
 - Up to 99.9% reliability (user configurable)
- RTK Initialization range
 - >40 km

TIME TO FIRST FIX^{1,6}

- Re-acquisition: 3 sec
- Hot start: 11 sec
- Warm start: 35 sec
- Cold start: 45 sec

I/O INTERFACE

- 100% compatible with MB500
- 30 pins SAMTEC TMM-115-03-G-D connector
- 1 Fast UART port (LV-TTL) up to 5 Mbits/sec
- 1 Fast UART port (LV-TTL) up to 921.6 kbits/sec
- 1 RS232 port up to 921.6 kbits/sec
- 1 USB 2.0 port up to 12 Mbits/sec
- 1 PPS output
- 1 Event marker input
- Onboard LED + output to drive external LED
- Antenna: female MMCX straight connector
- Reference Clock Input signal: female MMCX straight connector

PHYSICAL CHARACTERISTICS

- Size: 100x80x13 mm (3.9 x 3.1 x 0.5 in)
- Weight: 61 g/2.18 oz
- 100% compatible with MB500

POWER CHARACTERISTICS

- Input voltage: 3.3 to 9V DC
- Power consumption:
 - <1.9 W (GPS L1/L2)
 - <2.4W (GPS+GLONASS)
- Back-up power for RTC: 2.6 to 3.3V DC6
- Antenna(s) LNA power output: +5 VDC ($\pm 10\%$), Max current 100mA, Min current 5mA

ENVIRONMENTAL CHARACTERISTICS

- Operating temperature: -40° to +85°C (-40° to +185°F)
- Storage temperature: -40° to +85°C (-40° to +185°F)
- Humidity: 95% non-condensing
- Shock: MIL-STD 810F, Fig. 516.5-10 (40g, 11ms, saw-tooth)
- Vibration: MIL-STD 810F, Fig. 514.5C-17

RECOMMENDED ANTENNAS

- Compact GNSS Machine/Marine/Aviation Antennas: Trimble AV33 & AV34
- GNSS Machine/Marine/Aviation Antennas: Trimble LV59 & AV59

CONFIGURATION TOOL

Ashtech Communicator is a GNSS utility for boards and sensors evaluation and configuration.

- Preset of commands
- Real-time data logging
- Real-time data visualization

ORDERING INFORMATION

- MB800 is available in a variety of configurations
- ABX800 & ABX802 compact rugged sensor housing
- Evaluation Kit
 - Includes interface board and power supply

(* Including all available options

(1) Accuracy and TFF specifications may be affected by atmospheric conditions, signal multipath, satellite geometry and corrections availability and quality. Position accuracy specifications are for horizontal positioning. Vertical error is typically < 2 time's horizontal error.

(2) Performance values assume minimum of five satellites, following the procedures recommended in the product manual. High multi-path areas, high PDOP values and periods of severe atmospheric conditions may degrade performance.

(3) Steady state value for baselines < 50 km after sufficient convergence time.

(4) Typical values for properly installed antenna on vehicle body.

(5) For internal and external active antennas with automatic switch to external antenna when connected or for Heading determination between both antennas.

(6) Back-up battery may be used for RTC (Real Time Clock) to improve hot start TFF performances.



Specifications and descriptions are subject to change without notice.

©2014 Trimble Navigation Limited. All rights reserved. The Ashtech logo, the Z-Blade logo and MB100 are trademarks of Trimble Navigation Limited. All other product and brand names are trademarks of their respective holders. 11/2014

AMERICAS
TRIMBLE NAVIGATION LIMITED
Integrated Technologies
510 DeGuigne Drive
Sunnyvale, CA 94085 USA
+1-408-481-8000 Phone
Email: americasales-intech@trimble.com

EUROPE & MIDDLE EAST
TRIMBLE NAVIGATION LIMITED
Integrated Technologies
Germany
+49 (6142) 2100-348 Phone
France
+33 2 28 09 3800 Phone
Email: emeasales-intech@trimble.com

CHINA
TRIMBLE NAVIGATION LIMITED
Integrated Technologies
Email: chinasales-intech@trimble.com

ASIA - PACIFIC
TRIMBLE NAVIGATION LIMITED
Integrated Technologies
Email: asiasesales-intech@trimble.com

RUSSIA
TRIMBLE NAVIGATION LIMITED
Integrated Technologies
+49 (6142) 2100-348 Phone
Email: rusales-intech@trimble.com